

Damper actuators
Actuators for HVAC applications
Linear damper actuators 550 N: GBB..2E

Linear air damper actuators 550 N, without spring return

GBB..2E

- Button for disengaging the gear train to enable manual override
- With housing made of die-cast aluminium and 0.9 m connecting cable

Data sheet	N4656
Force	550 N
Air damper area	4 m ²
Nominal stroke	70 mm
Positioning time	150 s
Degree of protection	IP54
Dimensions (W x H x D)	100 x 298 x 67.5 mm



Range overview GBB...2E

Operating voltage [V]	Positioning signal	Power consumption	Auxiliary switch	Stock No.	Product No.
AC 24	3-position	7 VA / 7 W	0	BPZ:GBB131.2E	GBB131.2E
AC 24	3-position	7 VA / 7 W	2	BPZ:GBB136.2E	GBB136.2E
AC 230	3-position	8 VA / 5 W	0	BPZ:GBB331.2E	GBB331.2E
AC 230	3-position	8 VA / 5 W	2	BPZ:GBB336.2E	GBB336.2E
AC 24	DC 0...10 V	8 VA / 8 W	0	BPZ:GBB161.2E	GBB161.2E
AC 24	DC 0...35 V Adjustable	8 VA / 8 W	0	BPZ:GBB163.2E	GBB163.2E

Basic Documentation No.: Z4656